

AMENDMENT TO THE CLAIMS

1. (Currently amended) A reusable software block stored in a computer-readable memory ~~and adapted to control multiple instantiations of a peripheral device within a system~~, the reusable software block comprising:

a device hardware abstraction software layer adapted to configure multiple instantiations of a peripheral device within an integrated circuit, the hardware abstraction software layer defining offset values for registers of the peripheral device and defining a data structure for the peripheral device; and

a platform hardware abstraction software layer defining an address map of the system, the platform hardware abstraction software layer adapted to ~~initialize~~ configure each instantiation of the peripheral device via calls to the device hardware abstraction software layer.

2. (Currently amended) The reusable software block of claim 1 wherein the device hardware abstraction software layer comprises:

memory register locations adapted to be configurable during initialization of the system; and

an interrupt configuration, which is configured for the peripheral device during initialization of the system.

3. (Previously presented) The reusable software block of claim 2 wherein the memory register locations and the interrupt configuration define the data structure of the peripheral device using variables.

4. (Currently amended) The reusable software block of claim 1 wherein the data structure of the peripheral device is defined in the device hardware abstraction software layer using variables, the address map comprising:

memory locations associated with each instantiation of the peripheral device.

5. (Currently amended) The reusable software block of claim 4 wherein the platform hardware abstraction software layer initializes each memory location according to the memory map.

6. (Currently amended) The reusable software block of claim 1 wherein the data structure of the peripheral device is defined in the device hardware abstraction software layer using variables, the platform hardware abstraction software layer comprising:

an interrupt configuration corresponding to interrupt connections for a particular implementation of the peripheral device.

7. (Previously presented) The reusable software block of claim 6 wherein the interrupt configuration initializes each interrupt connection of the particular implementation of the peripheral device according to the interrupt configuration.

8-15. (Canceled)

16. (Currently amended) A system for instantiating multiple ~~instances~~ instantiations of a peripheral device within an integrated circuit, the system comprising a single configurable code block, which is stored in a computer-readable memory and comprises:

a device hardware abstraction software layer defining a configurable structure for the peripheral device; and

a platform hardware abstraction software layer adapted to configure the structure of each particular instantiation of the peripheral device via the device hardware abstraction software layer.

17. (Currently amended) The system of claim 16 wherein the device hardware abstraction software layer comprises:

memory register locations adapted to be configurable during initialization; and  
an interrupt configuration, which configures at least one interrupt connection for  
the peripheral device during initialization of the system.

18. (Previously presented) The system of claim 17 wherein the memory register locations and the interrupt configuration define the structure of the peripheral device using variables.

19. (Currently amended) The system of claim 16 wherein the configurable structure of the peripheral device is defined in the device hardware abstraction software layer using variables, the platform hardware abstraction software layer comprising:

a memory map of memory locations of the peripheral device corresponding to a  
particular implementation of the peripheral device, the memory map  
adapted to replace the variables with unique memory locations for each  
instantiation.

20. (Currently amended) The system of claim 16 wherein the configurable structure of the peripheral device is defined in the device hardware abstraction software layer using variables, the platform hardware abstraction software layer comprising:

an interrupt configuration corresponding to interrupt connections for a particular  
implementation of the peripheral device, the interrupt configuration  
adapted to replace the variables with values that define unique interrupt  
connections for each instantiation.